



Infor I-Supply Breed (IE)

AutoMap

Copyright © 2018 Infor

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements. As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: Infor I-Supply Breed

Publication date: July 2018

Contents

- Contents..... 3**
- Table of Changes 4**
- General Information 5**
- Security 7**
- Implementation..... 8**
 - Additional Records to Identify Destination as Issuer 8
 - Model Year Is Not Sent..... 9
 - Model Year IS Sent..... 9
- ASNS 11**
 - ASN Header Maintenance Screen..... 11
 - Flags/Codes Screen 11
 - ID Numbers Screen..... 11
 - Reference # Screen 12
 - ASN Detail Maintenance Screen 12
 - ASN Detail Reference Numbers Screen 12
- How to Use This Document..... 13**

Table of Changes

Changed By	Date	Reason	Update#	Section Changed

General Information

Transaction Sets

The I-Supply Breed module supports up to four (4) transaction sets. Your customer may or may NOT send or require all these transaction sets.

- 830 Material Release Version 4010
- 856 ASN Version 4010
- 862 Shipping Schedule Version 4010
- 997 Functional Acknowledgement Version 4010

The **830 (Material Release)** is intended to be used for planning requirements. However, at your customer's discretion, the 830 can be used for firm ship requirements, or for both planning and firm requirements, with the use of the type and frequency codes, assigned in the interface.

The **856 (ASN)** may be required to be transmitted for each shipment within the time frame defined by your customer.

The **862 (Shipping Schedule)** is intended to be used for firm ship requirements.

The **997 (Functional Acknowledgement)** may be required to be transmitted, by the supplier, to acknowledge the received files, within the time frame defined by your customer. The customer may send a 997 to acknowledge the 856 from the supplier.

Before You Get Started

Before I-Supply Breed map can be used, I-Supply Breed business practices must be known so that flags and keywords may be activated as necessary and master files are entered correctly.

1. How does I-Supply Breed identify you; with a DUNS, supplier code, etc.? You will use this information to establish the plant ID in the identification code file.
2. How does I-Supply Breed define itself? You will use this information to establish the OEM ID in the identification code file.
3. Do all destinations or divisions identify themselves in the same way? Does I-Supply Breed use different Issuer IDs for each destination or division when sending requirements? If so, how does I-Supply Breed identify each destination or division?

You will use this information to establish the OEM ID in the identification code file. If I-Supply Breed uses different Issuer IDs for each destination or division when sending requirements, "dummy" identification code records are needed. The unique destination IDs are entered in the OEM ID field in the identification code file.

4. Is a 997 required to be transmitted to I-Supply Breed to acknowledge receipt of the sent files? I-Supply Breed map is issued with the 997 auto transmit turned on. If I-Supply Breed does not

- require a 997 to be transmitted to acknowledge the received files this function may be turned off. Will I-Supply Breed send a 997 to acknowledge the 856 transmitted by the supplier?
5. Is I-Supply Breed sending model year? If so, what is the model year format? You will use this information to establish the requirement and price files.
 6. Is the 856 (ASN) required? What is the time frame for transmission? You will use this information to determine if the ASN field in the destination file needs to be marked and to create procedures to maintain a high quality rating. I-Supply Breed will monitor your performance based, in part, on the ASN. If the ASN is late, or not sent, your supplier rating may be affected.
 7. Are requirements sent with a RAN? Is the RAN more than 15 positions? Will multiple RANs be transmitted in the same file for the same customer, destination, part number, date, time, engineering revision level and purchase order number? If the RAN transmitted by I-Supply Breed is more than 15 characters it is truncated (all positions over 15 are dropped). You will use this information to determine the need to use the keyword "PROCDIFRAN A." If multiple RANs are transmitted in the same file this keyword MUST be active.
 8. Are requirements sent with a PO number? Is the PO number more than 15 positions? Is the purchase order number required to be transmitted in the ASN file? Will multiple purchase order numbers be transmitted in the same file for the same customer, destination, part number, date, time, engineering revision level and RAN? If the PO number transmitted by I-Supply Breed is more than 15 characters it is truncated (all positions over 15 are dropped). Are the first 15 characters of the PO number acceptable by I-Supply Breed? You will use this information to determine the need to use the keyword "PROCDIFFPO A." If multiple purchase orders are sent for the same file this keyword MUST be active.
 9. Are requirements sent with an engineering level? Is the engineering level more than 20 positions? Is the engineering level required to be transmitted in the ASN file? If the engineering level transmitted by I-Supply Breed is more than 20 characters it is truncated (all positions over 20 are dropped). Are the first 20 characters of the engineering level acceptable by I-Supply Breed?
 10. Will I-Supply Breed reject an ASN if specific segments are missing? What information has I-Supply Breed defined as "mandatory" in the ASN file? The I-Supply Breed has been coded based on AIAG standards. The ASN for I-Supply Breed map contains only warning messages. The supplier must know what fields are required. Your quality rating may be affected if required information is not returned in the ASN file. You may change warning errors to terminal errors so that the ASN transmission is halted if fields required by your customer are not present.
 11. What is the ASN cancellation procedure used by I-Supply Breed? You will use this information to establish procedures to maintain a high quality rating.

Security

Communication Method

I-Supply Breed communicates through the ACM (Advanced Communications Module) component.

For more information on ACM, see Chapter 17 of the AutoRelease main manual. Enter security requirements (identification codes, passwords, etc.) before attempting to receive or transmit. Network security is entered one time, but may be accessed by multiple trading partners.

Note: When establishing communication set up either with a VAN or direct, the following must exist:

Wrap Data? YES - 80

Start New Record on New Interchange? YES

File Archiving / Auto Print and Process

(Option 3 on the AZ10 Menu - ACM)

```
AZD2008                                PROCESS PROFILE SETUP

OEM .....
Company .....

Auto Print .....
Auto Process.....
Auto 997.....
Days To Archive.....

F4=Prompt   F12=Cancel
```

Auto Print (Y/N) - Enter “Y” if using Auto Receive and Breakdown (scheduled through ACM), to perform an automatic Print after the Breakdown. Enter “N” if not using Auto Receive, or, if using Auto Receive and Breakdown, if the Print option is not to be run automatically after the Breakdown.

Auto Process (Y/N) - Enter “Y” if using Auto Receive and Breakdown (scheduled through ACM) and if also using Auto Print, to perform an automatic Process after the Receive, Breakdown and Print. Enter “N” if not using Auto Receive, or, if using Auto Receive, Breakdown, and Auto Print, if the Process option is not to be run automatically after the Print.

Auto 997 (Y/N) – Enter “Y” and a 997 will automatically be sent back to the OEM acknowledging receipt of inbound EDI data.

Days to Archive - Enter the number of days to archive files received from the OEM. Files must be saved at least one day. Archived files are files that are stored for a given number of days, so that they can be reactivated. The number of days is not based on calendar days. Only the number of days when a communication session takes place is counted. Then the archived files are removed during the next shift.

Note: Only error-free requirements are processed. Errors must be corrected and the “Print” and “Process” options must be taken manually to process the remaining data.

Implementation

Identification Code File

The Identification Code File is used when taking the option to "Split" a file received from the trading partner and when transmitting ASNs. The Identification Code File is used differently by different manufacturers.

Initial Record

Company Number	- xx
OEM Code	- IE
Plant ID	- Mutually-defined plant ID code

Press Enter to display remaining fields:

OEM ID	- The ID code used to identify your customer
Corporate ID	- Mutually-defined
Remit to Duns #	- Not used by I-Supply Breed
Transmission Mode	- P
Smart Labels	- N
Pallet Staging	- N
Bar Code File Transfer	- N
Variable Unwrap Print	- N
Automatic print of 997	- N
AutoMap	- Y

Errors that occur during the "Split" that indicate a code is missing from the Identification Code File are referring to plant ID or OEM ID.

AutoMap - Enter "Y" to place data in the AutoMap files (during the Split).

The trading partner business practices may be inconsistent from supplier to supplier. For example, the plant ID may be a DUNS number for one supplier and another code for another supplier.

Additional Records to Identify Destination as Issuer

If requirements are received, from the same customer, but the issuer IDs are different for each destination or division, additional identification code records are needed to identify the destination as the issuer.

Enter a separate record for each destination or division that transmits requirements using a unique Issuer ID. The first record contains your supplier code in the plant ID field. Each additional record contains a "dummy" ID in the plant ID field. Use any number except a real supplier identification code used by this or another trading partner.

Note: OEM IDs for each destination must be provided by your customer that is issuing the requirements.

Master File Entry for the I-Supply Breed Map

The entry of each master file is NOT explained in this document. Only the master files that require unique entry, to accommodate specific business practices for this trading partner are noted.

Model Year

Is I-Supply Breed sending model year in the LIN segment of the 830 or 862 file? Refer to the appropriate information below.

Model Year Is Not Sent

The model year is not sent. Therefore, the requirement and price files must be entered leaving the model year fields blank.

Model Year IS Sent

The model year is transmitted. Therefore, the requirement and the price files must be entered with a model year also.

The model year must be entered exactly as I-Supply Breed transmits it. The field is four positions, however, if I-Supply Breed does not transmit all four positions, then the master files must be created using only the positions transmitted by the I-Supply Breed.

Requirement File - Clear Flags

The requirement master clear flags should not be marked. Keywords are used to determine what to clear based on purpose codes.

Requirement File - Report Flags

The report flags are marked depending on the transaction sets received from I-Supply Breed. The report flags may be marked one of three ways:

When both 830s and 862s are received mark the 830 and 862 report flag.

866	862	830	850
_	X	X	_

When ONLY 830s are received mark the 830 report flag.

866	862	830	850
_	_	X	_

When ONLY 862s are received mark the 862 report flag.

866	862	830	850
_	X	_	_

CUM Required Prior

I-Supply Breed does not send CUM required prior so it must be entered manually before going live so the system can include ahead or behind figures in the package quantity. The CUM required prior is entered using the option Enter Manual Requirements. CUM required prior can be entered using F5 from the entry screen or it may be entered directly on the header screen.

Reports

"I_SUPPLY_BREED" is the trading partner name that is printed on all reports for the I-Supply Breed.

Hexadecimal Codes for the ASN and Outbound 997

If I-Supply Breed is not using the hexadecimal codes provided by Infor they need to be modified. Infor provided hexadecimal codes include:

- Sub Element Separator: A1 ~
- Data Element Separator: 5C *
- Segment Terminator: 0D space

To modify the hexadecimal codes:

1. Access the AutoMap main menu.
2. Take the Map Maintenance option.
3. Select the trading partner with 1 (select).
4. Select the 856 transaction set with 5 (segments).
5. Press F8 (enveloping).
6. The maintain trading partnership file is displayed. Modify the hexadecimal codes that are different than the Future Three provided hexadecimal codes.
7. Press ENTER. If an outbound 997 is used repeat steps 1 - 6 for the 997, replacing 856 with 997.

ASNS

ASN Cancellation Procedure

You, the supplier, must be aware of the ASN cancellation procedure that is used by I-Supply Breed.

ASN Fields

The only fields that are mandatory are the ASN purpose, ship date, shipment quantity, ASN unit of measure and release number. The other fields listed are defaulted because they are retrieved from existing files within AutoRelease. These fields are warning messages and will not halt the creation of the ASN file.

Note: If I-Supply Breed requires specific data in the ASN file and will reject the ASN if this data is missing, the warning messages may be changed to terminal messages based on the data that this customer has defined as "mandatory." Terminal messages will halt the creation of the ASN file so errors may be corrected and a file that will be rejected is NOT transmitted.

ASN Header Maintenance Screen

ASN Purpose	-	Mandatory. Transmitted in the BSN 01. O - Original 00
Equipment Description	-	Mandatory. Transmitted in the TD3 01.
Equipment Initial	-	Mandatory. Transmitted in the TD3 02.
Ship Date	-	Mandatory. Transmitted in the DTM 02.
Ship Time	-	Mandatory. Transmitted in the DTM 03.
Pick up Carrier	-	Mandatory. Transmitted in the TD5 03.
Conveyance Code 08.	-	Warning. Transmitted in the TD5 04, TD5 07 and TD5

Flags/Codes Screen

ASN Codes	-	V for variable length without bar code verification.
-----------	---	---

ID Numbers Screen

Supplier ID	-	Mandatory. Transmitted in the N1*04.
-------------	---	--------------------------------------

Reference # Screen

BOL - Warning. Transmitted in the REF*02.

Conveyance Bill - Warning. Transmitted in the TD3 03.

ASN Detail Maintenance Screen

Cust Part # - Mandatory. Transmitted in the LIN 03.

Shipment Qty - Mandatory. Transmitted in the SN1 02 and CTT 02.

Ship Net - Warning. Transmitted in the MEA 03.

Ship Gross - Warning. Transmitted in the MEA 03.

CUM Shipped - Warning. Transmitted in the SN1 04.

ASN Unit/Mea - Mandatory. Transmitted in the SN1 03.

ASN Detail Reference Numbers Screen

Release # - Mandatory. Transmitted in the REF 02.

Eng Revision # - Warning. Transmitted in the LIN 07.

ASN Container Review Screen

Container Description - Warning. Transmitted in the TD1 01.

Container Qty - Warning. Transmitted in the TD1 02.

How to Use This Document

This document provides information regarding unique instructions required to implement this trading partner's unique business practices. There is a separate document called "AutoMap Manual" which describes those procedures which apply to all trading partners (NOT unique for each trading partner) such as the daily procedures, job controls, etc.

General Information

The general information section of this document describes transaction sets, how they apply to this trading partner and other miscellaneous information.

Security

The security section of the document explains the network(s) used by this trading partner, and specific information about how to create the trading partner cross reference file.

Implementation

Requirements received via AutoMap are processed into the AutoRelease master files to perform shipping, ASN and invoicing functions. Therefore, enter all master files in the same manner as required when processing data from the AutoRelease menus.

Exception: Special AutoMap processing needs are handled via keywords in AutoMap. Therefore, clear flags and special processing flags (F20) should not be marked.

The entry of each master file is NOT explained in this supplement. Only those that require specific fields marked to accommodate specific business practices for this trading partner are noted.

The master files required during the "process" from the AutoMap Requirement Display, are the same files that are required when processing from the VL0 menus:

- Machine Readable - customer and destination
- Parts Cross Reference
- Requirement Master

These files must be entered to successfully process data into the requirement and load files.

ASNs

All AutoMap trading partners transmit ASNs to the trading partner by using option 3 (ASNs) from the AutoMap menu. The ASN section of each trading partner document describes the ASN cancellation procedure and mandatory ASN fields for a specific trading partner.

A complete description of the common options can be found in the ASN section of the AutoMap manual.

AutoMap Features and Preferences

In AutoMap, keywords are unique for the business practices of the trading partner. This section describes how to access keywords, whether there are optional or conditional keywords for this trading partner, and how to activate and deactivate keywords.

Activate or Deactivate Keywords - Change Error Types (Warning - Terminal)

Keywords activate special processing to accommodate the OEM's practices. To view these keywords:

1. Access the AutoMap Menu.
2. Take the Process Keywords options.
3. Select the trading partner with 7 (keyword options).
4. Keywords are displayed for the selected trading partner.
5. Select the keyword to be changed with 1 (select).

The error maintenance screen displays. The fields that can be changed include:

Error Type - The error type may be W (warning) or T (terminal).

T (terminal) - When the create and transmit ASNs option is taken the ASN records are checked for missing fields that may cause the ASNs to be rejected. If terminal errors are found, (errors that will cause the ASN to be rejected according to OEM specifications) the program ends, the ASN Verification Report prints and a break message is displayed. Terminal errors must be corrected before taking the create and transmit option again.

W (warning) - When the create and transmit ASNs option is taken the ASN data is verified. If only warning errors are found, the ASN Verification Report prints and a break message is displayed that gives the user the option to continue with errors or to cancel. Error Message - The message that is displayed when this error is encountered may be changed.

Active - The keyword may be active (Y) or inactive (N).